



# Non-Cycling Refrigerated Dryers

28.3-68-m<sup>3</sup>/min, 1,000-2,400  
cfm

## Features

- **Reliable Clean, Dry Air:** Patented stainless steel heat exchangers are corrosion resistant and permit optimal heat transfer, resulting in a consistent pressure dew point
- **Lower Energy Costs:** Low pressure drop design saves on energy costs and provides an economical drying solution for your compressed air needs
- **Smart Control:** Easy to use, advanced microprocessor automatically manages dryer operation for optimum air treatment and maximum energy efficiency
- **Superior Equipment Protection:** Moisture and contamination are removed from the air stream via a high efficiency separator reducing downstream equipment problems
- **Eco-friendly Refrigerant:** Environmentally friendly R404A refrigerant meets all regulations and standards



## Model Specifications

Model	Capacity m <sup>3</sup> /min (scfm)	Operating Power kW	Length x Width x Height mm (in)	Weight kg (lb)	Connection Air In/Out
D1700IN	28.3 (1,000)	6.5	1,829 (72) x 813 (32) x 1,753 (69)	771 (1,700)	4" FLG
D2040IN	34.0 (1,200)	9.5	1,829 (72) x 813 (32) x 1,753 (69)	782 (1,725)	4" FLG
D2720IN	45.3 (1,600)	11.3	1,829 (72) x 813 (32) x 1,753 (69)	816 (1,800)	4" FLG
D3400IN	56.6 (2,000)	13.8	2,311 (91) x 813 (32) x 2,311 (91)	1,111 (2,450)	6" FLG
D4080IN	68.0 (2,400)	16.2	2,311 (91) x 813 (32) x 2,311 (91)	1,134 (2,500)	6" FLG



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit [www.ingersollrand.com](http://www.ingersollrand.com).