



## Sierra Oil-Free Rotary Screw Air Compressors 37-75 kW

Sierra oil-free rotary screw compressors are ISO 8573-1:2010 Class 0 certified, delivering 100% oil-free for the most critical applications. With an efficient and robust design, these compressors are a reliable workhorse that ensure the productivity of your business.

### Features

- **100% Oil-Free Air:** Meets ISO 8573-1:2001 Class 0 specifies air quality standards for processes within the food and beverage, pharmaceutical, textile, and electronics industries
- **Enhanced Reliability:** Stainless steel components, dual-vented seals, and precision machined-rotors with advanced UltraCoat protection ensure trouble-free operation
- **Smart Control to Reduce Energy Costs:** Easily accessible Xe-145 microprocessor controller provides continuous monitoring and on-board diagnosis to help optimize power consumption
- **Reduced Lubricant Change-Out:** Industry-leading Ultra Coolant delivers up to 8,000 hours of lubricant run time, as much as 8 times the life of conventional lubricants
- **High Ambient Operation:** Long-life components are designed to withstand 46°C maximum ambient temperature



# Model Specifications

Model	Frequency (Hz)	Nominal Power Kw (hp)	CAPACITY-FADm3/min (cfm)	Rated Pressure bar g (psig)	L X W X H cm (in)	Weight KG(LB) AIR-Cooled/Water-Cooled
SL37	50	37 (50)	6.0 (212)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2387 (5263) / 2410 (5314)
SL45	50	45 (60)	7.7 (272)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2248 (5506)/ 2520 (5556)
SL55	50	55 (75)	9.6 (339)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2577 (5682) / 2600 (5733)
SL75	50	75 (100)	12.7 (448)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2682 (5914) / 2705 (5965)
SM37	50	37 (50)	5.1 (180)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2387 (5263) / 2410 (5314)
SM45	50	45 (60)	6.5 (230)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2248 (5506)/ 2520 (5556)
SM55	50	55 (75)	8.8 (311)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2577 (5682) / 2600 (5733)
SM75	50	75 (100)	11.6 (410)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2682 (5914) / 2705 (5965)
SH55	50	55 (75)	7.7 (272)	10.0 (150)	225 (89) x 137 (54) x 192 (75)	2577 (5682) / 2600 (5733)
SH75	50	75 (100)	10.7 (37)	10.0 (150)	225 (89) x 137 (54) x 192 (75)	2682 (5914) / 2705 (5965)
L50	60	37 (75)	6.1 (216)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2318 (5110) / 2318 (5110)
L60	60	45 (60)	7.6 (268)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2433 (5364) / 2433 (5364)
L75	60	55 (75)	9.5 (336)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2433 (5364) / 2433 (5364)
L100	60	75 (100)	12.0 (424)	7.0 (100)	225 (89) x 137 (54) x 192 (75)	2495 (5500) / 2495 (5500)
H50	60	37 (75)	5.3 (186)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2318 (5110) / 2318 (5110)
H60	60	45 (60)	6.6 (232)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2433 (5364) / 2433 (5364)
H75	60	55 (75)	8.2 (290)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2433 (5364) / 2433 (5364)
H100	60	75 (100)	11.6 (411)	8.5 (125)	225 (89) x 137 (54) x 192 (75)	2495 (5500) / 2495 (5500)
HH75	60	55 (75)	7.6 (268)	10.0 (150)	225 (89) x 137 (54) x 192 (75)	2433 (5364) / 2433 (5364)



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR) driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit [www.IRCO.com](http://www.IRCO.com).

					225 (89) x 137 (54) x 192 (75)	2433 (5364)
HH100	60	75 (100)	11.1 (390)	10.0 (150)	225 (89) x 137 (54) x 192 (75)	2495 (5500) / 2495 (5500)