



## Single Stage Electric Driven Reciprocating Air Compressor 3-5 hp

Designed for any environment, our 3 and 5 hp single stage compressors are ideal for almost anyone, from individuals that thrive on do-it-yourself projects to the professional air compressor user. When performance is defined by maximum operating pressure, increased air flow and extended duty cycles, Ingersoll Rand is the product of choice. You will get a compressor that features maximum air power, reliable precision engineered components and a durable design that is built to last.

### Features

- Long-Life: Durable cast iron construction, long-lasting extended pump life designed for over 5,000 hours of trouble-free use
- Maximum Power and Flexibility: 100% continuous duty, high pressure operation up to 135 psig and a 60 gallon vertical ASME receiver tank provide plenty of punch for the most demanding applications
- Easy Operation: Automatic start/stop pressure switch control, fully assembled and pre-wired delivery, easy to change filter, oil site gauge and easy to fill oil port simplify operation and maintenance
- Advanced Safety Features: Manual thermal overload protection of the motor and a totally enclosed belt guard provide constant protection
- Reliable Operation: All Season Select synthetic lubricant increases efficiency; with 2,000 hours of service between changeouts, it performs four times longer than petroleum-based lubricants
- Two-Year Warranty Available: Purchase an All-Season Select lubricant start-up kit, and receive all the parts you need for start-up and the first year of maintenance, along with an extended pump warranty



#### Air Compressor Assistant

Unsure of which type of air compressor you need?  
Let us help find the right one for you.



Get Started →

## Model Specifications

Model	SS3L3	SS4L5	SS5L5	
Flow at 90 psi (cfm)	11.3	14	18.1	
Max Pressure (psig)	135	135	135	
Nominal Power (hp)	3	5	5	
Flow at Max Pressure (cfm)	10.3	10.8	15.5	
Base Length (in)	24	24	24	
Base Width (in)	25	25	30	
Base Height (in)	67	67	73	
NPT Outlet (in)	0.5	0.5	0.5	
Voltage/Engine	230/1/60	230/1/60	230/1/60	
Tank (gal)	60 Gallon Vertical	60 Gallon Vertical	60 Gallon Vertical	
Weight (lbs)	300	300	310	

## Parts & Accessories



**Small Reciprocating Start-Up Kits**



**Small Reciprocating Maintenance Kits**



**Small Reciprocating Gasket Kits**



**Small Reciprocating Valve Kits**



**Small Reciprocating Air Filter Elements**



**Electronic Drain Valves**



**SimplAir Compressed Air Piping**



**F-Series Filters**



**Air Compressor Tanks**



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit [www.ingersollrand.com](http://www.ingersollrand.com).